

Micrometer

The origin of Mitutoyo's trustworthy brand of small tool instruments

Coolant Proof Micrometers SERIES 293 — with Dust/Water Protection Conforming to IP65 Level

MeasurLink[®] ENABLED
Data Management Software by Mitutoyo

- World's highest performing micrometer overall.
- Extended battery life of approximately 2.4 years.
- Ergonomic anti-slip frame cover and front panel for more comfortable hand-held measurements.
- Ratchet thimble provides better operability for one-handed operation.
- Oil-resistant material used for all plastic parts.
- Models equipped with a Digimatic output port can form part of a statistical process control or networked measurement system. (Refer to page A-3 for details.)
- Interface Input Tools are available that enable the conversion of measurement data to keyboard signals that are then directly input to cells in off-the-shelf spreadsheet software such as Excel. (Refer to page A-13 for details.)
- Two types of constant-force devices are available: Ratchet Stop and Ratchet Thimble.
- Measuring faces: Carbide.



293-230-30



293-252-30



293-234-30
With ratchet thimble

MeasurLink[®] ENABLED
Data Management Software by Mitutoyo

Products equipped with the measurement data output function can be connected to the measurement data network system MeasurLink (refer to page A-5 for details).



These marks indicate that a product has successfully passed IP65-level testing, which is carried out by the independent German certification organization TÜV Rheinland.



An inspection certificate is supplied as standard. Refer to page X for details.

IP Codes

Level 6: Dust-proof.

No ingress of dust allowed.

Level 5: Protected against water jets.

Water projected in jets against the enclosure from any direction shall have no harmful effects.

Technical Data

Flatness:	0.3 μm /0.000012 in
Dust/water protection level:	IP65 (IEC60529)*1
Measuring force:	5 to 10 N (ratchet thimble type is 7 to 12 N.)*2
Battery:	SR44 (1 pc), 938882 , for initial operational checks (standard accessory)
Battery life:	Approx. 2.4 years under normal use
Length standard:	Electromagnetic rotary sensor
Standard accessories:	Reference bar, 1 pc (except for 0-25 mm (0-1 in) models) Spanner (301336), 1 pc

*1 Rustproofing shall be applied after use.

*2 Refer to page B-6 for details.

Optional Accessories

(Only for models with data output function)

Connecting cables with output switch

1 m: **05CZA662**

2 m: **05CZA663**

USB Input Tool Direct

USB-ITN-B (2 m): **06AFM380B**

Wireless data output **U-WAVE[™] fit**

U-WAVE-TM 264-622 (IP67 type)

264-623 (Buzzer type)

Connecting unit for U-WAVE-TM

02AZF310 (IP67 type)

Refer to page A-15 for details



SPECIFICATIONS

Functions

Origin point setting (ABS measurement system):

Resets the ABS origin at the current spindle position to the minimum value of the measuring range and switches to ABS mode.

Zero-setting (INC measurement system):

A brief press on the ZERO/ABS button sets display to zero at the current spindle position and switches to the incremental (INC) measuring mode. A longer press resets to the ABS measuring mode.

Hold:

Pressing the HOLD button freezes the current value in the display. This function is useful for preserving a measurement in situations of poor visibility where the instrument must be moved away from the workpiece before the reading can be recorded.

Data output*1:

Models equipped with this function have an output port for transferring measurement data to a Statistical Process Control (SPC) system.

*1: Only models with the data output function

Auto power ON/OFF:

The reading on the LCD disappears after this instrument is idle for about 20 minutes, but the reading and measurement mode are retained. Turning the spindle causes the reading to reappear.

Error alarm:

In case of an overflow on the LCD or a computing error, an error message appears on the LCD, and the measuring function stops. This prevents an instrument from giving an erroneous reading. Also, when the battery voltage drops to a certain level, the low-battery-voltage alarm annunciator appears well before the micrometer becomes unusable.

Function lock:

This function allows the ORIGIN (origin point setting) function and the ZERO (zero-setting) function to be locked to prevent these points being reset accidentally.

Metric

	Order No	Range	Resolution	Accuracy*	Parallelism	Constant-force device	Mass	
with SPC data output	293-230-30	0 - 25 mm	0.001 mm	±1 µm	1 µm	With ratchet stop	270 g	
	293-231-30	25 - 50 mm					330 g	
	293-232-30	50 - 75 mm			470 g			
	293-233-30	75 - 100 mm			625 g			
	293-250-30	100 - 125 mm		600 g				
	293-251-30	125 - 150 mm		740 g				
	293-252-30	150 - 175 mm		800 g				
	293-253-30	175 - 200 mm		970 g				
	293-254-30	200 - 225 mm		1100 g				
	293-255-30	225 - 250 mm		1270 g				
	293-256-30	250 - 275 mm		1370 g				
	293-257-30	275 - 300 mm		1590 g				
	293-234-30	0 - 25 mm		±1 µm	1 µm		With ratchet thimble	280 g
	293-235-30	25 - 50 mm						340 g
293-236-30	50 - 75 mm	480 g						
293-237-30	75 - 100 mm	635 g						
without SPC data output	293-240-30	0 - 25 mm	0.001 mm	±1 µm	1 µm	With ratchet stop	270 g	
	293-241-30	25 - 50 mm					330 g	
	293-242-30	50 - 75 mm		±2 µm	2 µm		470 g	
	293-243-30	75 - 100 mm					625 g	
	293-244-30	0 - 25 mm		±1 µm	1 µm		With ratchet thimble	280 g
	293-245-30	25 - 50 mm						340 g
	293-246-30	50 - 75 mm		±2 µm	2 µm		480 g	
	293-247-30	75 - 100 mm					635 g	

* Excluding quantizing error of ±1 count

Note: All digits of models over 125 mm (5 in) measuring range are presettable.

Inch/Metric

	Order No	Range	Resolution	Accuracy*	Parallelism	Constant-force device	Mass			
with SPC data output	293-330-30	0 - 1 in	0.0005 in /0.001 mm	±0.0005 in	0.00004 in	With ratchet stop	270 g			
	293-331-30	1 - 2 in					330 g			
	293-332-30	2 - 3 in			470 g					
	293-333-30	3 - 4 in			625 g					
	293-350-30	4 - 5 in		±0.0001 in	0.00012 in		600 g			
	293-351-30	5 - 6 in					740 g			
	293-352-30	6 - 7 in			800 g					
	293-353-30	7 - 8 in			970 g					
	293-354-30	8 - 9 in		±0.00015 in	0.00016 in		1100 g			
	293-355-30	9 - 10 in					1270 g			
	293-356-30	10 - 11 in		±0.0002 in	0.0002 in		1370 g			
	293-357-30	11 - 12 in					1590 g			
	without SPC data output	293-334-30		0 - 1 in	0.0005 in /0.001 mm		±0.0005 in	0.00004 in	With ratchet thimble	275 g
		293-335-30		1 - 2 in						335 g
293-336-30		1 - 2 in	±0.0001 in	0.00008 in		With ratchet stop		270 g		
293-340-30		0 - 1 in						330 g		
293-341-30		1 - 2 in	±0.0001 in	0.00008 in			With ratchet thimble	470 g		
293-342-30		2 - 3 in						625 g		
293-343-30		3 - 4 in	±0.0005 in	0.00004 in		280 g				
293-344-30		0 - 1 in				340 g				
293-345-30		1 - 2 in	±0.0001 in	0.00008 in		With friction thimble	480 g			
293-346-30		2 - 3 in					635 g			
293-347-30		3 - 4 in	±0.0005 in	0.00004 in			275 g			
293-348-30		0 - 1 in					275 g			

* Excluding quantizing error of ±1 count

Note: All digits of models over 125 mm (5 in) measuring range are presettable.

DIMENSIONS

Unit: mm

Range	Order No.	L	a	b	c	
0-25 mm	293-230-30/293-240-30	0	6.5	25	2.5	
25-50 mm	293-231-30/293-241-30	25	7.3	32.5		
50-75 mm	293-232-30/293-242-30	50	10.1	47		
75-100 mm	293-233-30/293-243-30	75	11.5	60		
0-25 mm	293-234-30/293-244-30	0	6.5	25		
25-50 mm	293-235-30/293-245-30	25	7.3	32.5		
100-125 mm	293-250-30	100	16.7	76		5.3
125-150 mm	293-251-30	125	18.8	90		5.7
150-175 mm	293-252-30	150	19.1	103		6.1
175-200 mm	293-253-30	175	18.2	115		6.3
200-225 mm	293-254-30	200	16.8	126		6.7
225-250 mm	293-255-30	225	18	139		5.5
250-275 mm	293-256-30	250	18	152		6.5
275-300 mm	293-257-30	275	18	166		6.5