



TDS-3

RANGE	0-9990 ppm Temp: 1-80°C / 33-176°F
ATC	YES
ACCURACY	± 2%
RESOLUTION	1ppm
CALIBRATION	Screw type
POWER	2 x LR44
SIZE	15.5 x 3.1 x 2.3 cm (6.1 x 1.25 x 1.0 in)
WEIGHT	77g/2.7oz (with case)



AP-1

RANGE	0-5000ppm Temp: 1-80°C / 33-176°F
ATC	YES
ACCURACY	± 2%
RESOLUTION	1ppm
CALIBRATION	Digital
POWER	1 x CR2032
SIZE	15.0 x 2.8 x 1.3 cm (5.9 x 1.1 x 0.5 in)
WEIGHT	43g/1.5oz (with batteries)



AP-2

RANGE	0-9990µS Temp: 1-80°C / 33-176°F
ATC	YES
ACCURACY	± 2%
RESOLUTION	1µS
CALIBRATION	Digital
POWER	1 x CR2032
SIZE	15.0 x 2.8 x 1.3 cm (5.9 x 1.1 x 0.5 in)
WEIGHT	43g/1.5oz (with batteries)



TDS-4TM

RANGE	0-9990 ppm Temp: 1-80°C / 33-176°F
ATC	YES
ACCURACY	± 2%
RESOLUTION	1ppm
CALIBRATION	Screw type
POWER	2 x LR44
SIZE	14.0 x 2.3 x 1.5 cm (5.5 x 0.9 x 0.9 in)
WEIGHT	34g/1.9oz (with batteries)



COM-80

RANGE	0-9999µS/ 0-9.9mS 0-5000ppm Temp: 1-80°C / 33-176°F
ATC	YES
ACCURACY	± 2%
RESOLUTION	1µS; 0.1mS 1ppm; 0.1°C/F
CALIBRATION	Digital
POWER	3 x LR44
SIZE	15.3 x 3.2 x 1.8 cm (6.0 x 1.3 x 0.7 in)
WEIGHT	55g/1.9oz (with batteries)



PH-80

RANGE	0.0 - 14.0 pH Temp: 1-80°C / 33-176°F
ATC	YES
ACCURACY	± 0.1pH
RESOLUTION	0.1 pH; 0.1°C/F
CALIBRATION	Auto at 4, 7, 10 pH
POWER	3 x LR44
SIZE	15.3 x 3.2 x 1.8 cm (6.0 x 1.3 x 0.7 in)
WEIGHT	65g/2.3oz (with batteries)