



HM-200

RANGE
 pH: 0.0~14.0pH
 EC: 0~9990 μ S/0~20mS
 TDS: 0~9990ppm
 Temp: 0~55°C/
 32~130°F

ACCURACY
 pH: ± 0.1 pH
 EC: $\pm 2\%$
 TDS: $\pm 2\%$
 Temp: $\pm 1^\circ\text{C}$ / $\pm 1.8^\circ\text{F}$

RESOLUTION
 pH: 0.1pH
 EC:
 0.1 μ S (0~99.9)
 1 μ S (100~999)
 10 μ S (1000~9990)
 0.01mS (0.01~20.00)
 TDS:
 0.1ppm (0~99.9)
 1ppm (100~999)
 10ppm (1000~9990)
 Temp: 0.1°C/°F

ATC YES

CALIBRATION Digital

POWER 2 x AA

SIZE 14 x 6.6 x 2.8 cm
(5.5 x 2.6 x 1.1 in)

WEIGHT 198g/7.0oz

FEATURES

- pH / EC / TDS / temperature measurement
- 5 units: pH, μ S, mS, ppm 0.5 (NaCl) Scale & 0.7 (442TM) Scale
- Automatic Temperature Compensation Function (ATC)
- Digital calibration
- Large readability LCD screen
- Simultaneous display of three measured values of pH / EC or TDS / temperature
- Replaceable sensors
- Included Accessories: Protective cover, 2 AA batteries, pH 4 & 7 calibration solution, pH preservation solution



Removable Cover



Portable



Backlit



Rugged Body