

HI97725

Free and Total Chlorine, Cyanuric Acid and pH Portable Photometer

for Legionella Protection

- Advanced LED optical system
 - Innovative optical design that utilizes a reference detector and focusing lens to eliminate errors from changes in the light source and from imperfections in the glass cuvette.
 - LEDs have a much higher luminous efficiency, providing more light while using less power. They also produce little heat, which could otherwise affect electronic stability.
- CAL Check™
 - Validate instrument performance at any time using CAL Check cuvettes made with NIST traceable standards.
 The CAL Check screen guides the user step-by-step through the validation process and user calibration.
- On-screen tutorial mode with animations
 - · Guides users step-by-step through the measurement process
- Waterproof and floating IP67 case
- Unit of measure is displayed along with reading
- Built-in timer
 - Built-in reaction timer that ensures consistency between tests.
- Error messages on display
 - Alerts to problems including no cap, high zero, and standard too low

- GLP data
- Displays the last calibration date.
- Auto logging
- Battery status indicator
- Auto-shut off

Legionella

Legionella species is the agent that causes human Legionnaires' disease as well as the lesser form, Pontiac Fever. Transmission is facilitated by the inhalation of mist droplets containing the Legionella bacteria.

Common sources of Legionella include cooling towers used in industrial cooling water systems as well as in large central air conditioning systems, domestic hot water systems, fountains, and similar disseminators that draw from a public water supply. Natural sources include freshwater ponds and creeks.

Since Legionella is especially harmful to people with weakened immune systems, it should be actively checked for in the water systems of hospitals and nursing homes.

Range Resolution	0.00 to 5.00 mg/L (ppm)
Resolution	
	0.01 mg/L
Chlorine, Free Accuracy @25°C (77°F)	±0.03 mg/L ±3% of reading
Method	adaptation of the EPA recommended DPD method 330.5 and standard method 4500-CL G
Range Resolution Accuracy @25°C (77°F) Method	0.00 to 5.00 mg/L (ppm)
	0.01 mg/L
	±0.03 mg/L ±3% of reading
	adaptation of the EPA recommended DPD method 330.5 and standard method 4500-CL G
Cyanuric Acid Resolution Accuracy @25°C (77°F)	0 to 80 mg/L (ppm)
	1mg/L
	±1 mg/L ±15% of reading
Method	adaptation of the Turbidimetric method
Range	6.5 to 8.5 pH
Resolution	0.1 pH
Accuracy @25°C (77°F)	±0.1 pH
Method	Phenol Red method
Light Source	light emitting diode
Bandpass filter	525 nm
Bandpass filter bandwidth	8nm
Bandpass filter wavelength accuracy	±1.0 nm
Light Detector	silicon photocell
Cuvette type	round 24.6 mm diameter (22 mm inside)
Auto logging	50 readings
Display	128 x 64 pixel B/W LCD with backlight
Auto-off	after 15 minutes of inactivity (30 minutes before a READ measurement)
Battery type / Life	alkaline 1.5 V AA (3) / > 800 measurements (without backlight)
Environment	0 to 50°C (32 to 122°F); 0 to 100% RH, non-serviceable
Dimensions	142.5 x 102.5 x 50.5 mm (5.6 x 4.0 x 2.0")
Weight	380 g (13.4 oz.)
and instruction manual. CAL Check standards and testing reagents HI97725C includes photome	mple cuvettes (2), sample caps (2), plastic stoppers (2), 1.5V AA batteries (3), instrument quality certificate, s sold separately ster, CAL Check standards, sample cuvettes (2), sample caps (2), plastic stoppers (2), 1.5V AA batteries (3), eck standard certificates, instrument quality certificate, instruction manual, and rigid carrying case.
	HI97701-11 CAL Check standard cuvettes for free and total chlorine
	HI93701-01 free chlorine reagents for 100 tests
	HI93701-03 free chlorine reagents for 300 tests
	HI97710-11 CAL Check standard cuvettes for pH
	HI93710-01 pH reagents for 100 tests
HI97725	HI93710-03 pH reagents for 300 tests
	HI93711-01 total chlorine reagents for 100 tests
	HI93711-03 total chlorine reagents for 300 tests
	HI97722-11 CAL Check standard cuvettes for cyanuric acid
	HI93722-01 cyanuric acid reagents for 100 tests
	HI93722-03 cyanuric acid reagents for 300 tests
	Resolution Accuracy @25°C (77°F) Method Range Resolution Accuracy @25°C (77°F) Method Range Resolution Accuracy @25°C (77°F) Method Range Resolution Accuracy @25°C (77°F) Method Light Source Bandpass filter Bandpass filter Bandpass filter wavelength accuracy Light Detector Cuvette type Auto logging Display Auto-off Battery type / Life Environment Dimensions Weight H197725 is supplied with sar and instruction manual. CAL Check standards and testing reagents H197725C includes photome cuvette wiping cloth, CAL Check

